

300 Series Regulators

307 Series Regulator

Single Stage

Rear Inlet

Chrome-Plated Brass Barstock Body

Four-Port Configuration

The 307 Series regulators are intended for secondary pressure control of non-corrosive, high purity or liquefied gases or as point of use pressure control in high purity gas distribution systems.

Advanced Features

- Chrome-plated brass barstock body Smooth surface finish
- Rear panel-mountable Easy installation
- Pressure ranges 0-15 to 0-200 PSIG Broad range of applications
- 3000 PSIG inlet pressure rating Safe use with high pressure cylinders

Typical Applications

- · Bulk gas distribution systems
- · Gas and liquid chromatography
- · High purity carrier gases
- Zero, span, and calibration gases
- High purity chamber pressurization
- · Liquefied hydrocarbon gas control
- · Control of cryogenic gases



300 Series Advantage

- Capsule® seat Increased serviceability and life
- 316L stainless steel diaphragm No inboard diffusion
- Low wetted surface area
 Minimal purge requirements
- Field-adjustable pressure limit Safeguard downstream equipment
- Convoluted diaphragm
 Smooth pressure changes
- Compact design
 Easily transported and intetgrated into systems

Materials

Bod

Chrome-plated brass barstock

Bonnet

Chrome-plated die cast zinc

Seat

PTFE

Filter

10 micron sintered bronze

Diaphragm

316L stainless steel

Internal Seals

PTFE

Specifications

Maximum Inlet Pressure 3000 PSIG (210 BAR)

Temperature Range -40°F to 140°F (-40°C to 60°C)

Gauges

2" diameter chrome-plated

Ports

1/4" FPT

Helium Leak Integrity
1 x 10⁻⁸ scc/sec


Cv

0.1

Weight (307-3031-TF4) 2.9 lbs. (1.29 kg)

300 Series Regulators

Technical Information



Ordering Information

307		Α	В	С	D	-Inlet	Options
Series 307	Outlet Pressure	Outlet Gauge	Inlet Gauge	Outlet Assemblies	Assembly Gauges	Inlet Connections	Installed Options
	1: 0-15	0-30 PSIG	0: None	0: 1/4" FPT Port	0: Bare Body	000: ¼" FPT	None
	2: 0-30	0-60 PSIG		1: 1/4" MPT	1: Standard Assembly (PSIG/kPa Gauges)	TF2: 1/8" Tube	
	3: 0-50	0-100 PSIG		2: 1/4" Tube Fitting	2: Standard Assembly (BAR/PSIG Gauges)	TF4: 1/4" Tube	
	5: 0-100	0-200 PSIG		3: Diaphragm Valve 1/4" Tube Fitting		TF6: 3/4" Tube	
	6: 0-200	0-400 PSIG		4: Diaphragm Valve 1/4" MPT		M06: 6mm Tube	
	8: 2-15 LPM CO ₂	2-15 LPM Flowgauge		5: Needle Valve ¼" MPT		CGA DIN 477	
	9: Custom Calibration	Custom Flowgauge		6: 1/8" Tube Fitting		BS 341 and others available	
				7: 3/8" Tube Fitting		avallable	
				8: DISS Outlet			
				9: Diaphragm Valve 1/4" FPT			
				A: 3/8" BSP Right Hand Fitting			
				B: Diaphragm Valve 1/8" Tube Fitting			
				M: 6mm Tube Fitting			
				S: Diaphragm Valve 6mm Tube Fitting			