

1100 Series Specialized Use Regulator



High Pressure Delivery

Features


- Indirect Gas Flow Path
 - *Precise flow control*
- 36" Copper Tubing with 1/8" MNPT Outlet
 - *Installation flexibility*
- 2" PSI/kPa Pressure Gauges
 - *Economical package*

Material

- Forged Brass Body
- PTFE Seat
- Glass Wool Inlet Filter

Specification

- 3000 psi Max Inlet
- Temperature Range -40° to 140°F (-40° to 60°C)



806-1130 Shown

Gas Service	Stock Number	Inlet CGA	Delivery Range	Outlet Fittings	Pressure Gauges
Oxygen	806-1130	540	0-1000 PSIG	With 3/16" Flexible Copper Tubing 36" long with Parker Fitting which fits 1/8" female pipe thread.	1500 & 4000 PSIG
Hydrogen	806-1143	350	0-1000 PSIG		1500 & 4000 PSIG
Argon, WP Nitrogen, Helium	806-1135	580	0-1000 PSIG		1500 & 4000 PSIG
Nitrogen OP	806-1136	555	0-1000 PSIG		1500 & 4000 PSIG
Industrial Air	806-1189	590	0-1000 PSIG		1500 & 4000 PSIG

Gas Station Kits

Gas Station	830-7334	540
Gas Station	830-7335	580
Gas Station	830-7336	320
Gas Station	830-7340	350
Gas Station	830-7342	590

Gas Station Kits include 36" Pigtail, Manifold Block, Mounting Bracket, and CGA Adapter