



6520 Series Dual Stage Regulator

Medium-Heavy Duty Welding, Heating and Cutting

Features

- 2.5" (63mm) Neoprene® Diaphragm
 - *Steady pressure control*
- Medium-Large Seat Displacement
 - *Good flow capacity*
- 2 1/2" PSI/kPa Pressure Gauges
 - *Excellent visibility*

Material

- Heavy Forged Brass Body
- PTFE/PCTFE Seat
- 25 Micron Bronze Capsule® Filter

Specification

- 3000/5500 PSI Max Inlet
- Temperature Range -40° to 140°F (-40° to 60°C)



806-6520 Shown



Gas Service	Stock Number	Inlet CGA	Delivery Range PSIG	Outlet Fittings	Pressure Gauges
Oxygen	806-6520	540	0-200 PSIG	9/16-18 "B" RH Ext.	400 & 4000 PSIG
	806-6526	540	0-120 PSIG	9/16-18 "B" RH Ext.	200 & 4000 PSIG
Acetylene, Fuel Gas*	806-6522	300	0-15* PSIG	9/16-18 "B" LH Ext.	30 Redline & 400 PSIG
	806-6529	510	0-15* PSIG	9/16-18 "B" LH Ext.	30 Redline & 400 PSIG
Argon, Nitrogen, Helium	806-6523	580	0-200 PSIG	5/8 -18 "B" RH Int.	400 & 4000 PSIG
	806-6525	580	0-120 PSIG	5/8 -18 "B" RH Int.	200 & 4000 PSIG
Argon, Nitrogen, Helium	806-6528	680 (5500 PSIG Max.)	0-120 PSIG	5/8 -18 "B" RH Ext.	200 & 6000 PSIG
Air	806-6527	347 (5500 PSIG Max.)	0-120 PSIG	1/4" NPT (M)	200 & 6000 PSIG

* Acetylene can not be used over 15 PSIG