

6590 Series Pipeline Regulator



Medium-Heavy Duty Heating and Cutting at Point of Use

Features

- 2.5" (63mm) Convuluted Neoprene® Diaphragm
 - *Steady pressure control*
- Medium-Large Seat Displacement
 - *Good flow capacity*
- Capsule® Seat Assembly
 - *High cycle life*

Material

- Forged Brass Body
- PTFE Seat
- 20-35 Micron Bronze Capsule® Filter

Specification

- 200 PSI Max Inlet
- Temperature Range -40° to 140°F (-40° to 60°C)



5 YEAR WARRANTY
The CONCOA Capsule® is warranted for five years to be free of defects in materials and workmanship.

Gas Service	Stock Number	Inlet CGA	Delivery PSIG	Outlet Connection	Fits Station Valve*
Oxygen	806-6596	CGA 024	0-120 PSIG	9/16"-18 "B" RH Ext.	801-0233
Acetylene, Propylene, Propane, Natural Gas	806-6592	CGA 025	0-15 PSIG	9/16"-18 "B" LH Ext.	801-0601
Propylene*, Propane, Natural Gas	806-6599	CGA 025	0-40 PSIG	9/16"-18 "B" LH Ext.	801-0601
Oil Free Inert, Argon-Nitrogen, Helium-CO2	806-6595	CGA 034	0-120 PSIG	5/8"-18"B" RH Int.	801-0034
Gas Service	Stock Number	Inlet CGA	Flowrate CFH	Outlet Fittings	Fits Station Valve*
Argon, CO2	806-6591	CGA 034	Argon: 10-60/CO2: 10-55	5/8"-18"B" RH Int.	081-0034
Argon, Helium	806-6597	CGA 034	Argon: 10-60/ Helium: 30-200	5/8"-18"B" RH Int.	801-0034
	806-6590 (Gas Saver)	CGA 034	Argon: 10-60/ Helium: 30-200	5/8"-18"B" RH Int.	801-0034
Argon, CO2	806-6594 (Dual Flowmeter)	CGA 034	Argon: 10-60/CO2: 10-55	5/8"-18"B" RH Int.	801-0034

* Acetylene should not be used over 15 PSIG

* Not included.