## Cutting Tips

## **CONCOA/AIRCO Seat Acetylene Tips**







## Style 195 - 1 Piece

Medium preheat tip. It has a flared cutting orifice that provides a large, low velocity oxygen stream with one side milled flat. It can be used for hand-cutting rivet heads and bulkheads. Tip is angled 45°. (3 preheat flames)

Materials Thickness (Inches)	Tip Size	Stock Number	Preheat Flames
3/8	1	854-9501	3
1/2	2	854-9502	3
3/4	3	854-9503	3
1	4	854-9504	3
2	5	854-9505	3

Use with Torch Series Cutting Attachment or Hand Cutting Torch 4700, 4800, 5700, 5800, 3000, 9000, 9500, 9700





## Style 196 - 1 Piece

Flared cutting orifice that provides a large, low velocity oxygen stream for rivet washing. It has a heavy preheat. (6 preheat flames)

Stock Number	Tip Size	Cutting Attachment or Hand Cutting Torch	
854-9608	8		
<u>854-9610</u>	10	-	
854-9612	12	4700, 4800, 5800, 3000, 9000, 9500, 9700 —	
854-9614	14		



(Shown Actual Size)

**STYLES 124, 138, 144 & 164** The physical dimensions and appearance of these four styles are similar. The variations are in size and number of preheat orifices and the cutting oxygen bore size. All are made of high quality tellurium cooper and have a 3/4" (19 mm) diameter.

Hand Cutting Torches Series	Cutting Attachments Series	Machine Torch Series
3000, 7000, 9000, 9500 & 9700	3500, 4700, 4800, 5700 & 5800	4700 Series