

Advantium 2 Remote Alarm

Features

- High profile visible and audible notification
- Audible alarm silence function
- Two input channels and one output channel
- One general dry contact relay output
- Normally Open or Normally Closed switch compatibility
- Auto-reset when cylinders are replenished

Specifications

- **Audio**
93 db audible alarm
- **Power**
120 VAC or 220 VAC
- **Relay Contact**
Single pole, double throw (SPDT)
- **Relay Contact Rating**
.5 A@24 VDC
- **Dimensions**
3 1/4" x 6" x 2"
- **System Fuses**
Internal resettable poly-fuse
- **Connections**
Input connector (6-pin circular)
Relay output connector (4-pin circular)
- **Intrinsic Safety Barriers**
Required for flammable gas service or for use in hazardous environments



529-5106 shown

Ordering Information

Series	Description
529-5106-120	Single-System Remote Alarm (120V)
529-5106-220	Single-System Remote Alarm (220V)
529-5312	Intrinsic Safety Barriers for 526 or 527 Series Switchover Systems
529-5296	Intrinsic Safety Barriers for 522, 523, 536 or 537 AutoSwitch Systems
529-5316-XX	Cable Available in 3', 10', 25', 50' and 100' lengths. "XX" in Stock Number specifies length.

Contact CONCOA for pre-made patch cables

Advantium 1 Remote Alarm

Features

- High profile visible and audible notification
- Audible alarm silence function
- Two input channels and one output channel
- One general dry contact relay output
- Normally Open or Normally Closed switch compatibility
- Auto-reset when cylinders are replenished

Specifications

- **Audio**
93 db audible alarm
- **Power**
120 VAC or 220 VAC
- **Relay Contact**
Single pole, double throw (SPDT)
- **Relay Contact Rating**
.5 A@24 VDC
- **Dimensions**
3 1/4" x 6" x 2"
- **System Fuses**
Internal resettable poly-fuse
- **Connections**
Input connector (6-pin circular)
Relay output connector (4-pin circular)
- **Intrinsic Safety Barriers**
Required for flammable gas service or for use in hazardous environments



529-5135 shown

Ordering Information

Series	Description
529-5135-120	Protocol Station Remote Alarm (120V)
529-5135-220	Protocol Station Remote Alarm (220V)
529-5313	Intrinsic Safety Barriers for Protocol Alarm Stations
529-5316-XX	Cable Available in 3', 10', 25', 50' and 100' lengths. "XX" in Stock Number specifies length.

Contact CONCOA for pre-made patch cables